

Datum: 08.10.2018

**Beschreibung:** aTape BGB-G, Betongewebeband, Gelb  
**Description:** aTape BGB-G, Cloth tape, gelb

Identifikationsnummer: 12126/124/1  
Artikelnr. 501010

Struktur:

**Beschreibung:** PE-besichtets Gewebe, mit einem gut haftenden synthetischen Kautschukkleber beschichtet.

**Description:** PE-coated cloth, single side coated with a good adherent synthetic rubber based adhesive.

**Einsatz:** Abdichten und Verbinden von Rohrleitungen und Lüftungskanälen. Befestigen von Folien auf schwierigen Untergründen wie Putz oder Beton. Zum Bündeln und Verpacken.

**Application:** Sealing and linking of pipeslines and air-ducts. Fixing and covering films an difficult substrates such as plaster or concrete. For bundling and packaging.

Technische Daten / Technical Data	Wert / Value
Träger / Carrier	PE-beschichtetes Gewebe / PE-coated cloth
Mesh Summer der Fäden / sum of threads inch <sup>2</sup>	35
Gesamtdicke / total thickness	0.170mm
Klebstoffbasis / adhesive-base	Synthesekautschuk / synthetic rubber
Klebkraft / Peel adhesion	≥ 6.0 N/cm / ≥ 15.0 N/25mm
Oberflächenklebrigkeit / Tack	hoch / high
Reisskraft / Tensile strength	≥ 32 N/cm / ≥ 80N/25mm
Reissdehnung / Elongation	15%
Temperaturbereich / Temperature range	-30°C - +60°C
UV-Beständigkeit / UV-resistance	Begrenzt / Limited
Verarbeitungstemperatur / Working temperature	Empfohlen / Recommended >5°C - +40°C
Farbe / Colour	Gelb/Yellow
Kerndurchmesser / Core diameter	76mm
Lagerstabilität / Storage life 18°C / 55%RF	12 Monate / 12 Months Trocken / Dry +5°C - +25°C, UV-geschützt / UV-Protected

Die verwendeten Prüfmethode basieren auf anerkannten Normen wie DIN, AFERA, FINAT, PSTC oder internen Prüfmethode, die bei Bedarf angefordert werden können.

The used test methods are based on recognized specifications like DIN, AFERA, FINAT, PSTC or internal test methods, which may be presented on request.

Document without signature

This technical data sheet serves excluding the improvement of the technical information according to the today's state of our knowledge, nevertheless, contains no assurance of properties. Besides the information provided in this refers only to the indicated item. The shown technical properties refer to new material with the generally tolerances. All technical characteristics can be changed without pre advice. The customer must judge the suitability of the product for the intended use and purpose himself; in this respect atravis carries neither responsibility nor guarantee. Our technical advice is only an expression of our opinion. Although this is given according to our best of knowledge, it is neither a basis for nor representation or statements of facts. This is valid even if proprietary rights of a third party are involved. Against commercial customers our product liability is strictly limited to the value invoiced when purchased. The liability for secondary damages is excluded, also the liability for light to middle carelessness