

Datum: 08.10.2018

Beschreibung: aTape PAB-100, Papierabdeckband, 100°C
Description: aTape PAB-100, Crepe Paper, 100°C

Identifikationsnummer: 12122/124/1
 Artikelnr. 501040

Struktur:

Beschreibung: Einseitig mit einem vernetzten Kautschukkleber beschichtetes flachgekrepptes Papier.
Description: Single side coated with a crosslinked rubber adhesive low creped paper.

Einsatz: Verpacken, Abdecken, Bündeln, Fixieren. Ein universelles Band für Abdekarbeiten in der Farb- und Lackiertechnik.

Application: Masking, Packaging, Bundling, Fixation. General masking application in the paint and varnish technique.

Technische Daten / Technical Data	Wert / Value
Träger / Carrier	Krepppapier / Crepe Paper
Gesamtdicke / total thickness	0.140mm
Klebstoffbasis / adhesive-base	Naturkautschuk / Natural rubber, solvent based
Klebkraft / Peel adhesion	≥ 2.0 N/cm / ≥ 5.0 N/25mm
Oberflächenklebrigkeit / Tack	Hoch / High
Reisskraft / Tensile strength	≥ 28 N/cm / ≥ 70N/25mm
Reissdehnung / Elongation	5%
Temperaturbeständigkeit / Temperature resistance	100°C (1h)
UV_Beständigkeit / UV-resistance	Begrenzt / Limited
Witterungsbeständigkeit / Weather resistance	Begrenzt / Limited
Verarbeitungstemperatur / Working temperature	Empfohlen / Recommended >5°C
Farbe / Colour	Gelb / yellow
Rollenlänge / Roll length	50m
Kerndurchmesser / Core diameter	76mm
Lagerstabilität / Storage life 18°C / 55%RF	12 Monate / 12 Months Trocken / Dry +5°C - +25°C, UV-geschützt / UV-Protected

Die verwendeten Prüfmethode basieren auf anerkannten Normen wie DIN, AFERA, FINAT, PSTC oder internen Prüfmethode, die bei Bedarf angefordert werden können.

The used test methods are based on recognized specifications like DIN, AFERA, FINAT, PSTC or internal test methods, which may be presented on request.

Document without signature

This technical data sheet serves excluding the improvement of the technical information according to the today's state of our knowledge, nevertheless, contains no assurance of properties. Besides the information provided in this refers only to the indicated item. The shown technical properties refer to new material with the generally tolerances. All technical characteristics can be changed without pre advice. The customer must judge the suitability of the product for the intended use and purpose himself; in this respect atravis carries neither responsibility nor guarantee. Our technical advice is only an expression of our opinion. Although this is given according to our best of knowledge, it is neither a basis for nor representation or statements of facts. This is valid even if proprietary rights of a third party are involved. Against commercial customers our product liability is strictly limited to the value invoiced when purchased. The liability for secondary damages is excluded, also the liability for light to middle carelessness